

Pneumatic special oil

Art. No. 101135

Type No. 32



Exemplary illustration

For oil-mist lubricators, pneumatic tools and pneumatic systems.

Heavy-duty lubricating oil for hydraulic and pneumatic systems, type HVLP
acc. to DIN 51524, Part 3. Mineral oil based for high functional and operating reliability.

The high viscosity index of >140 permits several viscosity classes to be covered with one oil quality, so that smooth running is guaranteed even at very low temperatures.

Good corrosion protection, excellent resistance to ageing and special wear protection assure optimal working.

The oil contains no zinc compounds.

Technical data

Temperature range	-35 to 85 °C
Description	2.5 litre canister

Commercial data

Customs tariff number	27101983
Country of origin	DE
eCl@ss 5.1.4	23060101
eCl@ss 9.0	23060101
UNSPSC_Code_v190501	15121514
UNSPSC_CodeDesc_v190501	Spray lubricants

Minimum storage period

The minimum storage period is 3 years.

The prerequisite is proper storage in unopened original containers, not exposed to sunlight or rain, storage temperature up to 40 °C.

Our extensive practical experience has shown that our products do not lose their properties even if the above-mentioned period is considerably exceeded.

Once the containers have been opened, sufficient precautions must be taken to prevent the ingress of dust, dirt, water etc. and the contents must therefore be used up quickly.