

# Reducing nipple

Stainless steel 1.4408

**STAINLESS STEEL**

Art. No. 118933

Type No. REDNG3818ES4408



Exemplary illustration

## Technical data

|                  |                                        |
|------------------|----------------------------------------|
| Working pressure | max. 20 bar                            |
| Thread 1         | G 1/8 IT                               |
| Thread 2         | G 3/8 ET                               |
| L1               | 16.0 mm                                |
| a/f              | 18 mm                                  |
| Thread form      | parallel male thread and female thread |
| Standard thread  | DIN EN ISO 228-1                       |
| Version          | Hexagonal                              |

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).

## Commercial data

|                         |                             |
|-------------------------|-----------------------------|
| Customs tariff number   | 73072910                    |
| Country of origin       | CN                          |
| eCl@ss 5.1.4            | 22360606                    |
| eCl@ss 9.0              | 22560206                    |
| UNSPSC_Code_v190501     | 40173303                    |
| UNSPSC_CodeDesc_v190501 | Stainless steel pipe nipple |

## Material informations

|                            |                            |
|----------------------------|----------------------------|
| REACH SVHC1 substance name | no                         |
| CAS no. SVHC 1             | no CAS No.                 |
| RoHS materials notice      | RoHS compliant             |
| REACH Info                 | no SVHC substance included |

## Dimensions



|           |            |
|-----------|------------|
| <b>L1</b> | <b>a/f</b> |
| <b>mm</b> | <b>mm</b>  |
| 16.0      | 18         |

From thread size of 1 inch, we recommend using an adjustable open-end wrench.

To ensure a proper sealing of the cylindrical threads (G) and tapered threads (R/Rp) we recommend using a suitable sealant (e.g. hemp, sealing tape or suitable industrial adhesive).