

T-piece

black



Art. No. 133686

Type No. TFT 130-11234-S



Exemplary illustration

According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.


Technical data

| | |
|-------------------|---|
| Material | black malleable iron B350-10, design symbol A |
| Temperature range | -20 to 300 °C |
| Surface | black |
| Standard thread | ISO 7-1 |
| Thread 1 | Rp 1 1/2 IT |
| Thread 2 | Rp 3/4 IT |
| Thread 3 | Rp 1 1/2 IT |

Commercial data

| | |
|-------------------------|--------------------|
| Customs tariff number | 73071910 |
| Country of origin | CN |
| eCl@ss 5.1.4 | 37200106 |
| eCl@ss 9.0 | 22560202 |
| UNSPSC_Code_v190501 | 40174603 |
| UNSPSC_CodeDesc_v190501 | Cast iron pipe tee |

Dimensions



| Thread 1 | Thread 2 | Thread 3 | A | B | Z1 | Z2 |
|-------------|-----------|-------------|------|------|------|------|
| | | | mm | mm | mm | mm |
| Rp 1 1/2 IT | Rp 3/4 IT | Rp 1 1/2 IT | 38.0 | 44.0 | 19.0 | 29.0 |