

T-piece

black



Art. No. 133689

Type No. TFT 130-2012-S



Exemplary illustration

According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Technical data

Material	black malleable iron B350-10, design symbol A
Temperature range	-20 to 300 °C
Surface	black
Standard thread	ISO 7-1
Thread 1	Rp 2 IT
Thread 2	Rp 1/2 IT
Thread 3	Rp 2 IT


Commercial data

Customs tariff number	73071910
Country of origin	CN
eCl@ss 5.1.4	37200106
eCl@ss 9.0	22560202
UNSPSC_Code_v190501	40174603
UNSPSC_CodeDesc_v190501	Cast iron pipe tee

Material informations

REACH SVHC1 substance name	no
CAS no. SVHC 1	no CAS No.
RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

Dimensions



Thread 1	Thread 2	Thread 3	A	B	Z1	Z2
			mm	mm	mm	mm
Rp 2 IT	Rp 1/2 IT	Rp 2 IT	38.0	48.0	14.0	35.0