

Spiral hose and blow gun kit plastic

MAX
Art. No. 146091
Type No. SPPSKR10600PU


Exemplary illustration

Instantly operational hose set, consisting of a polyurethane spiral hose, a metered blow gun, a permanently attached pushbutton safety coupling I.D. 7.4 and galvanised steel plug nipple.

Technical data

Operating temperature	-10 to 60 °C
Max. operating pressure	11 bar
Thread	G 1/4
Type of connection	nipple I.D. 7.2
Hose size	10x6.5 mm
No. of coils	37
Service length max.	6 m
Coil O.D.	69 mm
Material	polyurethane (spiral hose)
Gun body	Polypropylene (PP)
Hand lever	polyamide with glass fibre (PA6 GF30)
Nozzle type	standard nozzle

Commercial data

Customs tariff number	84818079
Country of origin	IT
eCl@ss 5.1.4	27294101
eCl@ss 9.0	27294190
UNSPSC_Code_v190501	40142002
UNSPSC_CodeDesc_v190501	Air hoses

Spareparts

	Art. No.	Type No.
Spiral hose, fitting and kink protection spring, rotating, PU, G 1/4, hose Ø 10x6.5, PN at 23 °C max. 11 bar, length 6.0 m	158161	SP10600PU
Pushbutton safety coupling I.D. 7.4, rotating, Aluminium, G 1/4 IT, Operating pressure max. 12 bar, Temp. -20 °C to 70 °C	199979	DKSKIG14
Nipple for couplings I.D. 7.2 - 7.8, hardened / galv. steel, G 1/4 IT, Operating pressure 0 - 35 bar, Temp. -20 °C to 100 °C	107551	243.55 ST
Metered blow gun, Plastic, standard nozzle, connectable below, PN max. 12 bar, Push-in plug DN 7.2	129371	BPKRDUANW72