

Flange pressure reducer



Art. No. 146767

Type No. FDM200.FG.0-30I



Exemplary illustration

Single-stage type in pressed brass version in accordance with DIN EN ISO 2503, with shut-off valve and safety valve as well as pressure gauge each for cylinder content and working pressure.

Bottle pressure reducers are used to reduce a gas that has been compressed, liquefied and dissolved in a bottle at a certain filling pressure/upstream pressure to a much lower, as constant as possible back pressure/overpressure, as independently as possible of fluctuations in the upstream pressure and flow rate. Cylinder pressure reducers with connection to gas cylinders are suitable for reducing the pressure of various gases. They have a type approval in accordance with DIN EN ISO 2503 for welding, cutting and related processes. The connections are designed in accordance with DIN 477.

Technical data

Material	pressed brass
Min. temperature range	-20 °C
Max. temperature range	60 °C
Gas type	forming gas
Colour code	black
Cylinder connection	W21.8x1/14 LH
Hose connection	G 1/4 LH ET
Indicating range	0 - 300/400 bar
Min. flowmeter	0 l/min
Max. flowmeter	30 l/min

Areas of application: Mechanical engineering, electrical and automotive industry, welding technology

Commercial data

Customs tariff number	84811099
Country of origin	IT
eCl@ss 5.1.4	37011108
eCl@ss 9.0	37011108
UNSPSC_Code_v190501	41112404
UNSPSC_CodeDesc_v190501	Pressure regulator

Accessories

	Art. No.	Type No.
Pressure gauge housing protection cap made of Plastic, black, for Pressure gauge-Ø 63 mm, for Connection radial bottom / back	146838	MGSK.KS.63

Spareparts

	Art. No.	Type No.
Content pressure gauge for Cylinder pressure regulator, steel housing, neutral gases, G1/4 Connection radial bottom, 0-400 bar Ø63	146825	IMF.N.14.400.63
Flow meter for Cylinder pressure regulator, 0 - 30 l/min, Brass/Plastic	146831	DFMF.30
Replacement seal for Cylinder pressure regulator (Cylinder connection), Plastic	146832	EDF.KS
Hose connector incl. nut for Cylinder pressure regulator, for hose I.D. 6,5/7,2/9/9,8, G 1/4 left-hand thread, Brass	146836	STMF.14LH.MS
Regulation, adjusting screw for blocking valve, for cylinder pressure regulators, plastic	147571	ESS.AV