

Short reducer

stainless steel 1.4571 (DIN 2353)

STAINLESS STEEL

Art. No. 148709

Type No. ES 313-ZW-2



Exemplary illustration

Version with parallel thread and FKM seal.

Suitable for compressed air, liquids, natural gas and hydraulics.

Not suitable for nitrogen, oxygen, helium, hydrogen or welding gases!


Technical data

| | |
|-------------------|------------------------|
| Temperature range | -20 to 200 °C |
| Material | stainless steel 1.4571 |
| Sealant | FKM |
| PN | 315 bar |
| Female thread | G 3/8 IT |
| Male thread | G 3/4 ET |
| L1 | 26 mm |
| L2 | 16 mm |

Commercial data

| | |
|-------------------------|--------------------|
| Customs tariff number | 73072910 |
| Country of origin | PL |
| eCl@ss 5.1.4 | 27294290 |
| eCl@ss 9.0 | 27294290 |
| UNSPSC_Code_v190501 | 27131614 |
| UNSPSC_CodeDesc_v190501 | Pneumatic adapters |

Dimensions



| Female thread | Male thread | L1 | L2 | S | i1 |
|---------------|-------------|----|----|----|----|
| | | mm | mm | mm | mm |
| G 3/8 IT | G 3/4 ET | 26 | 16 | 32 | 12 |