


Connection cable

Art. No. 153697

Type No. 0240010215



Exemplary illustration

Commercial data

eCl@ss 5.1.4	27291501
eCl@ss 9.0	27291390
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance

The diagram shows the front panel of the EB 80 Net power supply unit. At the top left, there is a 'Made in Italy' label and a 'Power' switch. To the right of the switch is a 'Diagnostic signaling LED'. Below the switch is a 'Power' button. In the center, there is a large rectangular terminal block with two '+' signs. To the right of this block is a circular terminal labeled 'M8 Net'. Below the terminal block are two circular terminals labeled 'Power' and 'Earth'. To the right of these terminals is a circular terminal labeled 'M8 Power Supply'. At the bottom, there are two circular terminals labeled '4' and '2'. To the right of these terminals is a circular terminal labeled 'M8 Power Supply'.

Diagnostic signaling LED

EB 80 Net (M8 female connector)


- 1 = CAN H
- 2 = CAN L
- 3 = Token
- 4 = GND (Black)

Power Supply (M8 male connector)

Connection for node power supply and auxiliary valve power supply


- 1 = +24VDC bus (Brown)
- 2 = +24VDC valve (White)
- 3 = GND (Blue)
- 4 = GND (Black)

DIMENSION OF ADDITIONAL ELECTRICAL CONNECTION

[illegible]

M8 CONNECTOR FOR POWER SUPPLY

Pin	Cable color
1	Brown
2	White
3	Blue
4	Black




Code	Description
0240009060	M8 4-pin female connector for power supply, cable L = 3 m
0240009037	M8 4-pin female connector for power supply, cable L = 5 m
0240009058	M8 4-pin female connector for power supply, cable L = 10 m
0240009059	M8 4-pin female connector for power supply, cable L = 15 m
0240009P60 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 3 m
0240009P37 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 5 m
0240009P58 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 10 m
0240009P59 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 15 m

* Very flexible cables, class 6 according to IEC 60228

M8 PLUG




Code	Description
0240009039	Plug for M8 connector

M8 CONNECTOR WITH CABLE FOR CONNECTION BETWEEN EB 80 ISLANDS


Code	Description	Weight [g]
0240010201	M8-M8 4-pin male straight connector with shielded cable L = 1 m	45
0240010205	M8-M8 4-pin male straight connector with shielded cable L = 5 m	185
0240010210	M8-M8 4-pin male straight connector with shielded cable L = 10 m	330
0240010215	M8-M8 4-pin male straight connector with shielded cable L = 15 m	475
0240010220	M8-M8 4-pin male straight connector with shielded cable L = 20 m	620
0240010405 *	M8-M8 4-pin male straight connector with shielded cable H-FLEX CL6, L = 5 m	185
0240010410 *	M8-M8 4-pin male straight connector with shielded cable H-FLEX CL6, L = 10 m	330
0240010415 *	M8-M8 4-pin male straight connector with shielded cable H-FLEX CL6, L = 15 m	475
0240010420 *	M8-M8 4-pin male straight connector with shielded cable H-FLEX CL6, L = 20 m	620


* Very flexible cables, class 6 according to IEC 60228

N.B.: For correct operation of the entire EB 80 system, use M8-M8 pre-wired, twisted and shielded cables only.

M8 ADAPTER CABLE



Code	Description	Weight [g]
0240010350	M8-M8 4-pin female adapter cable with shielded cable L = 200 mm	16

N.B.: Cannot be used with cables for mobile laying (H-FLEX CL6)

SPARE PARTS
EB 80 ELECTRICAL CONNECTION INTERFACE OR-SEAL


Code	Description
02282R1003	EB 80 electrical connection interface OR-seal

Comes in 10-pc. packs

GASKET BETWEEN EB 80 BASE AND COVER BUS/SIGNALS


Code	Description
02282R1004	Kit of gaskets between EB 80 base and cover bus/signals

Comes in 10-pc. packs

EB 80 BUS/SIGNAL INTERFACE OR-SEAL


Code	Description
02282R1005	EB 80 BUS/Signal interface OR-seal

Comes in 10-pc. packs

VALVES
EB 80 - ADDITIONAL ELECTRICAL CONNECTION - E