

Adapter cable

Art. No. 153725

Type No. 0240010501



Exemplary illustration

Commercial data

eCl@ss 5.1.4	27291501
eCl@ss 9.0	27291390
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

REACH SVHC1 substance name	lead
CAS no. SVHC 1	7439-92-1
RoHS materials notice	RoHS compliant
REACH Info	contains SVHC substance


ACCESSORIES

M8 PLUG




Code	Description
0240009039	Plug for M8 connector

M8 CONNECTOR FOR DIGITAL INPUTS / OUTPUTS




Code	Description
0240009010	M8 3-pin straight connector

M8 CONNECTOR WITH CABLE FOR DIGITAL INPUTS / OUTPUTS




Code	Description
0240009009	M8-M8 3-pin straight connector with cable L = 3 m

M8 Y-CONNECTOR WITH CABLE FOR DIGITAL INPUT/OUTPUT




Code	Description
0240009048	Y-connector M8 4-pin M / double M8 3-pin F with cable L = 0.7 m

Note: Can only be used with S21 modules




M12 Y-CONNECTOR WITH CABLE FOR DIGITAL INPUT/OUTPUT




Code	Description
0240009049	Y-connector M12 4-pin M / double M12 4-pin F with cable L = 0.7 m

Note: Can only be used with S22 modules


VALVES
EB 80 - SIGNAL MODULES - S


M8 MALE CONNECTOR FOR ANALOGUE INPUTS/OUTPUTS



Code	Description
0240010300	M8 4-pin male connector

M8 CONNECTOR FOR POWER SUPPLY

Pin	Cable color
1	Brown
2	White
3	Blue
4	Black




Code	Description
0240009060	M8 4-pin female connector for power supply, cable L = 3 m
0240009037	M8 4-pin female connector for power supply, cable L = 5 m
0240009058	M8 4-pin female connector for power supply, cable L = 10 m
0240009059	M8 4-pin female connector for power supply, cable L = 15 m
0240009P60 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 3 m
0240009P37 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 5 m
0240009P58 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 10 m
0240009P59 *	M8 4-pin female connector for power supply, H-FLEX CL6, cable L = 15 m

* Very flexible cables, class 6 according to IEC 60228

90° M8 CONNECTORS WITH SHIELDED CABLE


Pin	Cable color
1	Brown
2	White
3	Blue
4	Black



Code	Description
0240009102	M8 4-pin female, 90° connector with shielded cable L = 2 m
0240009103	M8 4-pin female, 90° connector with shielded cable L = 5 m


M8 4-POLE MALE CONNECTOR

Pin	Cable color
1	Brown
2	White
3	Blue
4	Black



Code	Description
0240010105	M8 4-pin connector shielded cable L = 5 m


M8 3-POLE MALE – M12 5-POLE FEMALE CONNECTOR WITH CABLE FOR DIGITAL INPUTS/OUTPUTS



Code	Description
0240009045	M8 3-pole male straight - M12 5-pole female connector with cable L = 0.2 m

M8	M12
pin 1	pin 1
pin 4	pin 4
pin 3	pin 3


M8 4-POLE MALE – M12 8-POLE FEMALE CONNECTOR WITH CABLE FOR REGTRONIC CONNECTION



Code	Description
0240009046	M8 4-pole male straight - M12 8-pole female connector with cable L = 1 m


M8	M12
pin 1	pin 8
pin 2	pin 3
pin 3	pin 7
pin 4	disconnect

M8 CONNECTOR WITH SHIELDED CABLE FOR ANALOGUE INPUTS/OUTPUTS



Code	Description
0240005005	M8-M, M8-F 4-pole straight connector with shielded cable L = 1 m
0240005006	M8-M, M8-F 4-pole straight connector with shielded cable L = 3 m
0240005003	M8-M, M8-F 4-pole straight connector with shielded cable L = 5 m
0240005008	M8-M, M8-F 4-pole straight connector with shielded cable L = 10 m

M8 ADAPTER CABLE FOR CONNECTING THE PRESSURE SWITCH TO THE DIGITAL INPUTS MODULE




Code	Description
0240010501	M8-M, M8-F 3-pole adapter with cable L = 0.3 m

Note: Can be used for connecting 1/8-1/4, Syntesi[®], Skillair[®], PRS L pressure switches to the module of digital INPUT S01 of the EB 80 valves. Contact type NO (Normally-Open)

M8F	M8M	Function
pin 1	pin 1	Power supply +
pin 3	pin 4	Signal NO
pin 4	pin 3	Disconnect


M8 SHIELDED ADAPTER CABLE FOR CONNECTING THE LTS-LTL POSITION TRANSDUCERS TO THE ANALOGUE INPUTS MODULE



Code	Description
0240010601	M8-M, M8-F 4-pole adapter with shielded cable L = 0.3 m (blue collar)

Note: Can be used for connecting the 4/20 mA analog output of the LTL-LTS position sensors to the module of analog INPUT S04 of the EB 80 valves.

M8F	M8M	Function
pin 1	pin 1	Power supply +
pin 2	pin 2	Signal 4/20 mA
pin 3	pin 3	Power supply -
pin 4	disconnect	



Code	Description
0240010701	M8-M, M8-F 4-pole adapter with shielded cable L = 0.3 m (red collar)

Note: Can be used for connecting the 0/10 VDC analog output of the LTL-LTS position sensors to the module of analog INPUT S04 of the EB 80 valves.

M8F	M8M	Function
pin 1	pin 1	Power supply +
pin 4	pin 2	Signal 0/10 V
pin 3	pin 3	Power supply -
pin 2	disconnect	

ADDITIONAL FIXING BRACKET TO OMEGA BAR



Code	Description	Weight [g]
02282R4001	Additional fixing bar accessory to EB 80 Omega bar	5

Individually packed


N.B.: to be used to improve the fixing to Omega bars of islands with more than 10 modules. The bracket must be positioned every 5-6 modules.

NOTES

VALVES

EB 80 - SIGNAL MODULES - S

EB 80 BUS/SIGNAL INTERFACE OR SEAL




Comes in 10-pc. packs


Code	Description
02282R1004	Kit of gaskets between base and BUS/Signal cover



Code	Description
0226107000	Identification plate kit



Code	Description
02282R5010	Connector 12 positions for modules S06 and S07



RIEGLER & Co. KG
Schützenstraße 27
72574 Bad Urach
Tel. +49 7125 9497-642
technik@riegler.de