


Multi-pole cable

Art. No. 153734

Type No. 02269B0250



Exemplary illustration

Commercial data



eCl@ss 5.1.4	27291501
eCl@ss 9.0	27291390
UNSPSC_Code_v190501	40141603
UNSPSC_CodeDesc_v190501	Pneumatic valves

Material informations

RoHS materials notice	RoHS compliant
REACH Info	no SVHC substance included

ACCESSORIES

IP65 25-PIN PRE-WIRED PLUG CONNECTOR




Code	Description	Weight [g]
02269A0100	IP65 25-pin 90° connector, UL cable L = 1 m	180
02269A0250	IP65 25-pin 90° connector, UL cable L = 2.5 m	365
02269A0500	IP65 25-pin 90° connector, UL cable L = 5 m	680
02269A1000	IP65 25-pin 90° connector, UL cable L = 10 m	1220
02269A2000	IP65 25-pin 90° connector, UL cable L = 20 m	2350
02269C0100 **	IP65 25-pin 90° connector, UL H-FLEX CL6, cable L = 1 m	180
02269C0250 **	IP65 25-pin 90° connector, UL H-FLEX CL6, cable L = 2.5 m	365
02269C0500 **	IP65 25-pin 90° connector, UL H-FLEX CL6, cable L = 5 m	680
02269C1000 **	IP65 25-pin 90° connector, UL H-FLEX CL6, cable L = 10 m	1220

** Very flexible cables, class 6 according to IEC 60228

Position of electrical contact	Colour of the corresponding wire	Function
1	White	Out 1
2	Brown	Out 2
3	Green	Out 3
4	Yellow	Out 4
5	Grey	Out 5
6	Pink	Out 6
7	Blue	Out 7
8	Red	Out 8
9	Black	Out 9
10	Violet	Out 10
11	Grey + Pink ring	Out 11
12	Red + Blue ring	Out 12
13	White + Green ring	Out 13
14	Brown + Green ring	Out 14
15	White + Yellow ring	Out 15
16	Yellow + Brown ring	Out 16
17	White + Grey ring	Out 17
18	Grey + Brown ring	Out 18
19	White + Pink ring	Out 19
20	Pink + Brown ring	Out 20
21	White + Blue ring	Out 21
22	Brown + Blue ring	Fault reporting
23	White + Red ring	Config. PNP/NPN *
24	Brown + Red ring	+VDC
25	White + Black ring	0VDC

* Connect to +VDC if (Out) valves with a POSITIVE signal are to be controlled
Connect to 0VDC if (Out) valves with a NEGATIVE signal are to be controlled

IP65 44-PIN PRE-WIRED PLUG CONNECTOR



Code	Description	Weight [g]
02269B0100	IP65 44-pin 90° connector, UL cable L = 1 m	275
02269B0250	IP65 44-pin 90° connector, UL cable L = 2.5 m	630
02269B0500	IP65 44-pin 90° connector, UL cable L = 5 m	1180
02269B1000	IP65 44-pin 90° connector, UL cable L = 10 m	2210
02269B2000	IP65 44-pin 90° connector, UL cable L = 20 m	4340
02269D0100 **	IP65 44-pin 90° connector, UL H-FLEX CL6, cable L = 1 m	275
02269D0250 **	IP65 44-pin 90° connector, UL H-FLEX CL6, cable L = 2.5 m	630
02269D0500 **	IP65 44-pin 90° connector, UL H-FLEX CL6, cable L = 5 m	1180
02269D1000 **	IP65 44-pin 90° connector, UL H-FLEX CL6, cable L = 10 m	2210

** Very flexible cables, class 6 according to IEC 60228

Position of electrical contact	Colour of the corresponding wire	Function
1	White	Out 1
2	Brown	Out 2
3	Green	Out 3
4	Yellow	Out 4
5	Grey	Out 5
6	Pink	Out 6
7	Blue	Out 7
8	Red	Out 8
9	Black	Out 9
10	Violet	Out 10
11	Grey + Pink ring	Out 11
12	Red + Blue ring	Out 12
13	White + Green ring	Out 13
14	Brown + Green ring	Out 14
15	White + Yellow ring	Out 15
16	Yellow + Brown ring	Out 16
17	White + Grey ring	Out 17
18	Grey + Brown ring	Out 18
19	White + Pink ring	Out 19
20	Pink + Brown ring	Out 20
21	White + Blue ring	Out 21
22	Brown + Blue ring	Out 22
23	White + Red ring	Out 23
24	Brown + Red ring	Out 24
25	White + Black ring	Out 25
26	Brown + Black ring	Out 26
27	Grey + Green ring	Out 27
28	Yellow + Grey ring	Out 28
29	Pink + Green ring	Out 29
30	Yellow + Pink ring	Out 30
31	Green + Blue ring	Out 31
32	Yellow + Blue ring	Out 32
33	Green + Red ring	Out 33
34	Yellow + Red ring	Out 34
35	Green + Black ring	Out 35
36	Yellow + Black ring	Out 36
37	Grey + Blue ring	Out 37
38	Pink + Blue ring	Out 38
39	Grey + Red ring	Fault reporting
40	Pink + Red ring	Config. PNP/NPN *
41	Grey + Black ring	+VDC
42	Pink + Black ring	+VDC
43	Blue + Black ring	0VDC
44	Red + Black ring	0VDC

* Connect to +VDC if (Out) valves with a POSITIVE signal are to be controlled
Connect to 0VDC if (Out) valves with a NEGATIVE signal are to be controlled


VALVES

EB 80 - MULTI-POLE ELECTRICAL CONNECTION - E

B2

SPARE PARTS

EB 80 ELECTRICAL CONNECTION INTERFACE OR SEAL



Code	Description
02282R1003	EB 80 electrical connection interface OR seal

Comes in 10-pc. packs

NOTES

VALVES

EB 80 - MULTI-POLE ELECTRICAL CONNECTION - E

B2.32