



CPC HYDRAULIC OIL LPS

- CPC Hydraulic Oil LPS are high Quality hydraulic oils with low pour point.
- Contain anti-wear, antirust, antioxidant and anti-foaming additives with high viscosity index. Used under 5000psi pressure machine at wide temperature range.
- Package: 200 liter drum
- The typical data are listed as follow:

Grade No.	LPS32	LPS46	LPS68
Gravity, API, 15.6°C	31.6	30.4	29.5
Viscosity, Kin, cSt @40°C	31.45	47.01	70.0
@100°C	6.50	8.52	11.30
Viscosity Index	167	160	155
Pour Point, °C	-45	-42	-39
Flash Point, COC, °C	221	232	244
Color, D1500	1.5	1.5	L2.0
TAN, mgKOH/g	0.60	0.60	0.60
Carbon Residue, Rams.,%	0.16	0.17	0.17
Emulsion, 54°C, 40-37-3, min	15	15	15
Product No.	LA68032	LA68046	LA68068

Grade No.	LPS100	LPS150
Gravity, API, 15.6°C	28.6	27.6
Viscosity, Kin.,cSt @40°C	103.0	149.9
@100°C	14.40	17.53
Viscosity Index	144	128
Pour Point, °C	-36	-30
Flash Point, COC, °C	250	264
Color, D1500	2.5	L3.0
TAN, mgKOH/g	0.60	0.60
Carbon Residue, Rams., %	0.21	0.25
Emulsion, 82°C, 40-37-3, min	20	20
Product No.	LA68100	LA68150